

BV 1

- one-piece body ball valve, side entry
- reduced bore
- end connections according BSP or NPT
- face to face dimension according our production standard
- available in various body and seat material

SIZE: 8mm - 50mm / 1/4" - 2"



BV4 - DIN

- two-piece, split body ball valve
- true integral full bore
- flange connections according DIN 2501 / DIN 2526 - PN10/16/40
- face to face dimension according DIN 3202-F18 (F4/F5) & F1, EN 558-1-14/15 & 1
- available in various body, ball and stem material
- different seat material PTFE, RTFE, CTFE, MPTFE, PEEK,...
- trunion execution available on request

SIZE: DN15 - DN300



BV 6

- 3-way ball valve, L or T-bore
- reduced bore
- end connections according BSP or NPT
- face to face dimension according our production standard
- available in various body and seat material

SIZE: 8mm - 50mm / 1/4" - 2"



BV 2

- two-piece body ball valve
- full bore
- end connections according BSP or NPT
- face to face dimension according our production standard
- available in various body and seat material

SIZE: 8mm - 100mm / 1/4" - 4"



BV4 - ANSI

- two-piece, split body ball valve
- true integral full bore
- flange connections according ANSI B16.5
- face to face dimension according ANSI B16.10 - A-150/A-300
- available in various body, ball and stem material
- different seat material PTFE, RTFE, CTFE, MPTFE, PEEK,...
- trunion execution available on request

SIZE: 1/2" - 12"



BV 7

- one-piece body ball valve, side entry
- reduced or full bore
- flange connections according DIN 2501 / DIN 2526 - PN10/16, ANSI B16.5
- face to face dimension according DIN 3202-F18 (F4/F5), EN 558-1-14/15, ANSI B16.10 - A-150
- available in various body and seat material

SIZE: DN15 - DN200 / 1/2" - 8"



BV 3

- three-piece body ball valve
- full bore
- end connections according BSP, NPT, BW or SW
- face to face dimension according our production standard
- available in various body and seat material

SIZE: 8mm - 100mm / 1/4" - 4"



▪ ADR
▪ ANSI
▪ TA-LUFT
▪ PED

▪ FIRE SAFE
▪ ISO
▪ 3.1
▪ ATEX

▪ SIL
▪ KVBG/ARGB
▪ EN
▪ BS

▪ MTBF
▪ A/105
▪ GOST
▪ ROSTECHNADZOR

BV 8

- wafer one-piece body ball valve, side entry
- reduced or full bore
- flange connections according DIN 2501 / DIN 2526 - PN10/16, ANSI B16.5
- face to face dimension according our production standard
- available in various body and seat material

SIZE: DN15 - DN200 / 1/2" - 8"



overview products

WAFER – LUG RUBBERLINED

BV10



BV10-U
BV11
BV12-U



BV12



DOUBLE FLANGED

BV13



BV14



WAFER – LUG TFM LINED

BV10-TFM



BV12-TFM



HIGH PERFORMANCE

BV10-HP
BV12-HP
BV13-HP

